


ZONE 1 TRANSFORMER MODEL SERIES 30AH-ELPK-XFMRZ1 SPECIFICATIONS



Ex II 2G Ex eb IIB T4 Gb IP66



- ▶ IECEx TPS 21.0026X
 - Ex eb IIB T4 Gb
- ▶ TPS 22ATEX113825X
 - II 2G
 - Ex eb IIB T4 Gb IP66
- ▶ CE Mark and Notify Body No.


- ▶ AMBIENT TEMPERATURE RATING:
 - -20°C TO +45°C
- ▶ INGRESS PROTECTION:
 - IP66
 - Finger guard included
- ▶ TYPE OF PROTECTION:
 - Increased Safety “e”
- ▶ RATING*:
 - 60HZ, ±5%
 - 60KVA
 - 440VAC
 - 151A
 - Customized Configurations Available Upon Request
- ▶ * All ratings are customizable

MODIFICATION AND DESIGN OPTIONS

- ▶ CUSTOMIZED CONFIGURATIONS TO MEET DESIGN NEEDS:
 - Optional Ex db anti-condensation heater sub-assembly
 - Optional Ex eb temperature sensor sub-assembly
 - Custom mounting frames available as needed
- ▶ TRANSFORMER SIZES AVAILABLE:
 - 6kVA, 10kVA, 15kVA, 25kVA, 35kVA, and 60kVA
 - Enclosure sizes adjusted as needed per transformer size and end-user needs.
- ▶ DESIGN DOCUMENTS:
 - All drawings, general arrangements, and operations/maintenance manual information are supplied with all builds
 - Other custom design documents available upon request



- ▶ MATERIAL:
 - Enclosure constructed of 12 gauge 316L stainless steel
 - Electrical conductors of transformer windings are coated with a varnish resin wrapped in NOMEX paper
- ▶ COATING OPTIONS:
 - Powder Coating
 - Epoxy Coating